

Git

Alles hilfreiche zu Git.

- [Aliase für Git](#)

Aliase für Git

recentb

Recent branches of the current repository

You can put the following snippet in your `~/.gitconfig`. The `recentb` alias accepts two arguments:

- `refbranch`: which branch the *ahead* and *behind* columns are calculated against. Default *master*
- `count`: how many recent branches to show. Default *20*

```
[alias]
  # ATTENTION: All aliases prefixed with ! run in /bin/sh make sure you use sh syntax, not
  bash/zsh or whatever
  recentb = "!r() { refbranch=$1 count=$2; git for-each-ref --sort=-committerdate refs/heads
  --format='%(%(refname:short)|%(HEAD)%(color:yellow)%(refname:short)|%(color:bold
  green)%(committerdate:relative)|%(color:blue)%(subject)|%(color:magenta)%(authorname)%(color:r
  eset)' --color=always --count=${count:-20} | while read line; do branch=$(echo \"$line\" | awk
  'BEGIN { FS = \"|\" }; { print $1 }' | tr -d '*'); ahead=$(git rev-list --count
  \"${refbranch:-origin/master}..${branch}\"); behind=$(git rev-list --count
  \"${branch}..${refbranch:-origin/master}\"); colorline=$(echo \"$line\" | sed 's/^[^|]*|//');
  echo \"$ahead|$behind|$colorline\" | awk -F'|' -vOFS='|' '{ $5=substr($5,1,70)}1' ; done | (
  echo \"ahead|behind|branch|lastcommit|message|author\n\n\" && cat) | column -ts'|';}; r"
```

Result:

[Recentb alias result](#)